

トランシーバ規格対応表

| | | トランシーバ名(波長) 付属ATT | FTB-8590(850nm) | FTB-8190(1310nm) ATT 10dB | FTB-8193(1550nm) ATT 10dB | FTB-8592(1550nm) | FTB-8690(850nm) | FTB-8693(1310nm) | FTB-8694(1550nm) ATT 6dB |
|-----------------------------|-------------|----------------------|-----------------|------------------------------|------------------------------|------------------|-----------------|------------------|-----------------------------|
| 入力レベル(dBm) | | | -20~0 | -18~0 | -22~0 | -22~0 | -11.1~+0.5 | -11~+0.5 | -15.8~-1 |
| 出力レベル(dBm) | | | -9~-3 (MMF) | -5~0 | -5~0 | 0~+5 | -5~-1 | -6~-1 | -4.7~+4.0 |
| 伝送距離(MAX) | | | 550m | 15km | 40km | 90km | 300m | 10km | 40km |
| | | | SFP | | | | SFP+ | | |
| レート | 規格 | | | | | | | | |
| 1GE | 1000BASE-SX | ○ | | | | | | | |
| | 1000BASE-LX | | ○ | | | | | | |
| | 1000BASE-ZX | | | ○ | ○ | | | | |
| 10GE | 10GBASE-SR | | | | | ○ | | | |
| | 10GBASE-LR | | | | | | ○ | | |
| | 10GBASE-ER | | | | | | | ○ | |
| | 10GBASE-SW | | | | | ○ | | | |
| | 10GBASE-LW | | | | | | ○ | | |
| | 10GBASE-EW | | | | | | | ○ | |
| STM-64/OC-192 | | | | | | ○ | ○ | ○ | |
| STM-0/STM-1 STM-4/STM-16 | | | ○ | ○ | | | | | |